

## Granville FS-R 5W/30

1 Litre, 5 Litre, 20 Litre & 205 Litre

### PRODUCT DESCRIPTION

Granville FS-R 5W/30 is formulated using the very latest advanced additive technology and base oils. Manufactured to meet the latest performance demands of certain Renault vehicles requiring a low SAPs (sulphated ash, phosphorous and sulphur) content. Suitable for engines with diesel particulate filters fitted where this grade and specification is required.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C4

Renault: RN0720

MB: 226.51



\* Image for illustrative purposes only.

### PRODUCT BENEFITS

- \* Ensures lubricant performance over extended drain intervals
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficiency
- \* Effective environmental protection

### PRODUCT USAGE

For engines where this specification lubricant is required.

### DIRECTIONS FOR USE

As recommended by the engine manufacturer.

### STORAGE INSTRUCTIONS

Store Upright and sealed in a cool dry place, out of the reach of children.

SIZE	PART NO	BARCODE
1 Litre	0568	5020618005681
5 Litre	0569	5020618005698
20 Litre	0565	5020618005650
205 Litre	0571	5020618005711



# Granville FS-R 5W/30

1 Litre, 5 Litre, 20 Litre & 205 Litre

## SHELF LIFE

5 years from date of manufacture.

<b>Appearance</b>	: Amber liquid
<b>Odour</b>	: Characteristic
<b>Solubility</b>	: Insoluble in water
<b>Percentage of Base Oil</b>	: Less Than 80%
<b>Percentage of Biodiesel</b>	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	12.3
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.5
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			72.4
Density	ASTM D792	@ 15°C			0.85

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

